

XT LIGHTING DATASHEET: PL112W

PL112W Recessed LED Light with changeable faceplate.


TRI-CCT 3000K 4000K 5700K

- Input voltage range: 220-240V 50/60Hz
- Inbuilt constant current driver included
- Housing: aluminium & plastic
- Faceplate: White: plastic
- Faceplate: Satin chrome, matt black & brass: aluminium
- Diffuser: frosted PC
- Tri-CCT (3000K/ 4000K/ 5700K) in one fitting
- CCT switch on side
- LED chip: 20pcs SMD2835
- Power factor: 0.9
- CRI: ≥80
- Flex & plug: 600mm
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Suitable for use with sensors



Tested & Recommended Dimmers:

BRAND	PART NO.	PCS PER DIMMER				
CLA	LYNX	PL112: 1-10PCS				
CLIPSAL	32E450TM					
НРМ	CAT400T					
DIGINET	MEDM, MMDM/RT					



PL112

Statement of the statem

FACEPLATE line drawing



PL112W Box Includes:

- 1x Downlight (PL112W) with white faceplate
- 1x Loose Satin Chrome faceplate



PL112

Chome Faceplate

Available faceplates (Sold Separately):

- Matt Black (PL112FPB)
- Antique Brass (PL112FPAB)





PL112FPAB

PL112FPB

		LUMENS			WATT	PRODUCT DIMEN-	СИТ	вох	вох	CARTON
PART NO.	DESCRIPTION	3000К	4000K	5700K	WATT	SIONS (mm)	OUT (mm)	WEIGHT (kg)	DIMENSIONS (cm)	QTY
PL112W	D/L LED FIXED WH+S/C DIMM RND TRI	800lm	950lm	850lm	10	Ø112x56.5	Ø90	0.2	10.5x10.5x6.5	1/50
PL112FPB	FACEPLATE TO SUIT MATT BLK OD 112mm									
PL112FPAB	FACEPLATE TO SUIT ANTIQUE BRASS OD 112mm									